



# WIRELESS SWITCHES & REMOTES

PROJECT	
TYPE	PART#

## PRODUCT FEATURES

- Use with TILT® Low Voltage or 0-10V Wireless Controller
- Turns TILT® lights on/off and provides full range of dimming (5%-100%) with no flicker
- 4 programmable operating modes
- Easily programmed or reconfigured in minutes
- Up to 25 Switches and/or Remotes can be paired with one TILT® Controller
- Not affected by other wireless signals
- Available in single or double switch configurations and a variety of colors
- Mounting hardware included for installation in standard wall box or any hard surface
- 5-year warranty



## PART NUMBER & PRODUCT GUIDE (WIRELESS SWITCHES & REMOTES)

Product	Part#	Description	Mount Style	Modes	Temp Range	Power	Range
WSRC WSS WSD	WSRC WSS WSD	Switch used to dim or turn lights on/off	In a switch box or mount to a surface using the mounting plate	1- Rocker 2-Momentary 3-Toggle 4-Scene	14°F-140°F	Powered through the mechanical operation of the switch. No battery needed	150 Feet

\*See separate specification sheets for these compatible products

## COMPATIBLE TILT® CONTROLLERS\*

Product	Part#	Description	Mount Style	Temp Range	Power
	WLVD	Low Voltage Wireless Controller	On 24V DC power supply line with LED driver	13°F-140°F	24V DC, 10A max no battery
	W010	0-10V Wireless Controller	Mount to jbox or driver enclosure using knock-out. Run 0-10V wire to driver output.	32°F-122°F	100-277V AC input 500W-5A Max @ 110V 2000W-20 Max @ 100V

\*See separate specification sheets for these compatible products